


FULL-SIZE SERIES

Rough Terrain Scissor Lifts

Specifications	SJ 9250
A Work Height	56' (17.1 m)
B Raised Platform Height	50' (15.2 m)
C Lowered Platform Height	79" (2.0 m)
D Overall Width	92" (2.3 m)
E Overall Length	176" (4.5 m)
F Stowed Height (Rails Up)	124.5" (3.2 m)
G Stowed Height (Rails Down)	90" (2.3 m)
H Platform Width (Inside Dimension)	74" (1.9 m)
I Platform Length (Inside Dimension)	168" (4.3 m)
Ground Clearance	8" (0.2 m)
Wheelbase	119" (3.0 m)
Weight	14,970 lbs (6,790 kg)
Gradeability	30%
Turning Radius (Inside)	210" (5.3 m)
Turning Radius (Outside)	301" (7.7 m)
Lift Time (With Rated Load)	67 sec
Drive Speed (Stowed)	2 mph (3.2 km/h)
Drive Speed (Raised)	0.6 mph (1 km/h)
Maximum Drive Height	26' (7.9 m)
Capacity (Overall)	2,000 lbs (907 kg)
Maximum # of Persons	5



STANDARD FEATURES

- Axle based 4WD
- "Detroit Locker" type rear differential and limited slip front different
- Disc brake system on rear axle
- 65hp GM Dual fuel (gas/propane) engine on roll out tray
- Self-centering scissor design allows optional extension decks to be added to one or both ends
- Independent/auto leveling outriggers
- Analog control system
- Color coded and numbered wiring system
- 30% gradeability
- Grip lug, air-filled tires
- 110V AC outlet on platform with GFI
- Tilt alarm with drive & lift cut-out
- All motion audible alarm
- Flashing light
- Operator horn
- Fold down hinged railing system
- Half height spring hinged gates on both sides
- Lanyard attachment points
- Tie down/lift lugs

OPTIONS†

- 5' (1.5 m) powered extension deck (single or dual)
- 29hp Kubota Diesel engine (in lieu of std dual fuel)
- Diesel engine with scrubber (in lieu of std dual fuel)
- Shop airline to platform
- 3500W hydraulic generator
- Full height spring hinged gates
- Air-filled tires with tire sealant
- Grip lug foam-filled tires
- Non-marking grip lug air-filled tires
- Non-marking grip lug foam-filled tires

† Capacities, and machine weights may differ when options are added

Model	Capacity With 1 Extension Deck*		Capacity With 2 Extension Decks*		
	Main	Front Ext.	Main	Front Ext.	Rear Ext.
SJ 9250	1,000 lbs (454 kg)	500 lbs (227 kg)	500 lbs (227 kg)	500 lbs (227 kg)	500 lbs (227 kg)

This brochure is for illustrative purpose only and based on the latest information at the time of printing. Skyjack Inc. reserves the right to make changes at any time, without notice, to specifications, standard and optional equipment. Consult the Operating Maintenance and Parts Manuals for proper procedures. Work platforms have been tested to comply with ANSI and CSA standards as interpreted by Skyjack, Inc.

